

Job/Project \_\_\_\_\_  
 Location \_\_\_\_\_  
 Fixture Ref. \_\_\_\_\_  
 Quantity \_\_\_\_\_  
 Remarks \_\_\_\_\_

## Product Description

Use high-performance SMD LED, Ra>80. Aluminum heatsink and unique die casting heatsink design ensure better heat dissipation.

## Luminaire

Structure Fixed Down Light LED  
 Model No. IBSP221  
 Wattage 3-7W  
 Luminous Flux >180lm-420lm  
 Beam 15° | 24° | 38° | 50°  
 24° | 36°  
 IP Ratings IP20  
 Material Die casting aluminum heatsink  
 Finish White | black

## Installation

Suitable for 5~18 mm thick ceiling board

## LEDs

Brand Osram | Cree  
 Type SMD  
 Color Temp 2700K | 3000K | 3500K | 4000K  
 5000K | 5700K | 6500K  
 CRI 80 | 90


## Control Gear

Remote constant current LED driver  
 Brand Eaglerise | Lifud | OEM  
 Input Voltage 220~240Vac | 100-240Vac  
 Dimming Non Dim | Dim  
 Remarks Flicker-free, PF 0.5 | 0.9

## Photometrics



Ra>80



## Picture

